



DRIVESHAFT ANDERSON, INC.



30 mm x 47 mm x 9 mm SKF 61906 deep groove ball bearings

Bearing No. 61906

61906 Bearing 2D drawings and 3D CAD models

Size	47x30x9 mm
Bore Diameter	47 mm
Outer Diameter	30 mm
Width	9 mm
d	30 mm
D	47 mm
B	9 mm
d ₁	35.25 mm
D ₂	42.7 mm
r _{1,2} - min.	0.3 mm
d _a - min.	32 mm
D _a - max.	45 mm
r _a - max.	0.3 mm
Basic dynamic load rating - C	7.3 kN
Basic static load rating - C ₀	4.6 kN
Fatigue load limit - P _u	0.212 kN
Reference speed	30000 r/min
Limiting speed	19000 r/min
Calculation factor - k _r	0.02
Calculation factor - f ₀	14.4
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A



DRIVESHAFT ANDERSON, INC.

Weight / Kilogram	0.051
EAN	7316577095022
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	30MM Bore; 47MM Outside Diameter; 9MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	61906
Weight / LBS	0.11
Outside Diameter	1.85 Inch 47 Millimeter
Bore	1.181 Inch 30 Millimeter
Outer Race Width	0.354 Inch 9 Millimeter
bore diameter:	30 mm
static load capacity:	4.55 kN
outside diameter:	47 mm



DRIVESHAFT ANDERSON, INC.

precision rating:	Not Rated
overall width:	9 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	9 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
maximum rpm:	19000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	7.28 kN
d_1	35.25 mm
D_2	42.7 mm
$r_{1,2}$ min.	0.3 mm
d_a min.	32 mm
D_a max.	45 mm
r_a max.	0.3 mm
Basic dynamic load rating C	7.28 kN
Basic static load rating C_0	4.55 kN
Fatigue load limit P_u	0.212 kN
Calculation factor k_r	0.02
Calculation factor f_0	14.4
Mass bearing	0.049 kg